

415 24V

24V Electromechanical operator



Max width single leaf

2,5 - 4 m

Use frequency

Continuous use



- "In-axis" thrust operator.
- Available in versions with a 300 mm (max leaf 3 m) and 400 mm (max leaf 4 m) rod stroke.
- Horizontal exit for cables to allow near to ground installation (low installation).



**24V SAFEzone
system:**
415 24V + E024S or
E124



**24V GREENtech
system:**
415 24V + E124



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	415 24V	415 L 24V
Power supply voltage	220-240V~ 50/60 Hz	220-240V~ 50/60 Hz
Motor	With brushes 24V	With brushes 24V
Max. power	70 W	70 W
Max expressed force	2800 N	2800 N
Rod max speed	16 mm/s	16 mm/s
Rod travel	300 mm	400 mm
Max. leaf opening angle	110°	110°
Operating ambient temperature	-20°C ÷ +55°C	-20°C ÷ +55°C
Protection class	IP54	IP54
Weight	7,8 Kg	8 Kg
Use frequency	Continuous use	Continuous use
Max. leaf width	2,5 m (3 with electric lock)	3 m (4 with electric lock)
Mounting brackets	Rear attachment to be welded/screwed - front attachment to be welded	
Dimensions (LxDxH)	835 x 105 x 148 mm	940 x 105 x 148 mm
Electronic equipment	Not included	Not included